

Ready-wired Pressure Switches



Applications

Our pressure switches mostly have a degree of protection IP 65. This may not be adequate for all applications. Especially for commercial vehicles, mobile hydraulics, and similar applications where IP 67 or IP 6K9K may be required.

At SUCO any commercially-available connector system can be supplied ready-wired with a customer-specific cable length. This ensures great flexibility, and we can also supply small quantities without the need for expensive tooling.

The technical data of ready-wired pressure switch variants are substantially the same as those of the standard models. Differences in the technical data will be agreed with the customer and defined on a customer-specific drawing of the ready-wired pressure switch.

Pressure-switches suitable for ready-wiring

are supplied with the switching point preset in our works. The switching point can not be changed subsequently. It is therefore essential that the switching point is stated when the order is placed.

Pressure switches in the **0240/0241** range can be adjusted after wiring

Pressure-switch ranges suitable for ready-wiring



0263/0266
0267
0269

See page 12-16, 18 for technical data



0268

See page 17 for technical data



0270/0271
0290/0291
0296/0297

See page 23, 26, 28 for technical data



0240/0241

See pages 22 and 33 for technical data

A selection from the wide variety of plugs we can supply.



Plugs to
DIN 72585

BOSCH plugs
(Jet plugs)

Cannon
plugs

AMP
plugs

Packard
plugs
(Weather Pack)

Packard
plugs
(Weather Pack)

Deutsch
plugs
(DT 06)

Deutsch
plugs
(DT 04 – 2P)

Deutsch
plugs
(DT 04 – 3P)

Further plugs and connectors available on request

We supply the type and length of cable you need